

	COMMERCIAL REFERENCES AND FEATURES	Ø VALVE HOLE AND VALVE HEIGHT	TUBULAR DIMENSIONS AND RECOMMENDED PRESSURE	GLUING AND MAINTENANCE
<p>WHEEL</p>	<ul style="list-style-type: none"> Internal unidirectional carbon fiber structure and external woven carbon fiber form. 5 spoke structure with rotation direction. Aerodynamic wing-shaped internal and external structures. 	<p>Ø 6,5 mm</p> <p>Valve extension M40013.</p>	<p>Ø 700 633 mm Section : 18 - 21 mm.</p> <p>Ø 650 584 mm Section : 18 - 21 mm.</p> <p>MAX. : 15 BAR / 215 PSI MIN. : 7 BAR : 100 PSI.</p>	<p>Gluing : see page 56.</p> <p>Cleaning : Use a dry cloth or soap and water.</p> <p>Do not use solvents.</p>
<p>HUB</p>	<ul style="list-style-type: none"> Anodized, lightweight alloy body. Sealed, removable adjustable cartridge bearings. Aluminum alloy axle. Spacing : 100 mm. 	<p align="center">ADJUSTING THE BEARINGS</p> <p>Fasten the wheel to the frame and put the bike on the ground :</p> <p>1 - If there is free play : slightly tighten the bearing adjustment nut with the tool provided (delivered with the wheel) checking the free play at the top of the wheel.</p> <p>2 - If there are tight bearings : loosen the bearing adjustment nut about 1/2 turn, unfasten the wheel, remove it from the frame. Lightly hit the bearing adjustment nut side of the axle with a mallet until the axle rotates freely, refasten the wheel to the frame and adjust it as previously described.</p> <p><i>The hub of a iO® wheel has been pre-adjusted at the factory for optimum use and long life. However, free play can be modified. Free play mis-adjustments can damage the bearings on the iO® wheel or seriously alter their performance.</i></p>	<p align="center">MAINTENANCE</p> <p>Cleaning : Use a dry cloth or soap and water. Do not use pressurized water.</p> <p>Maintenance : see pages 36 - 50.</p>	
<p>TRACK FIXING BOLT</p>	<p>WHEEL DELIVERED WITH :</p> <ul style="list-style-type: none"> Track fixing bolt M40124 Quantity per package : 2 screws CHC M6 + 2 fork supports. <ul style="list-style-type: none"> Bag : M40135 Instructions Warranty coupon 	<p align="center">TECHNICAL INFORMATION</p> <ul style="list-style-type: none"> Steel screw CHC M6 Anodized aluminum alloy fork supports 	<p align="center">INSTALLING</p> <p>Lubricate the bolt threads before installing.</p>	