










## TECHNICAL FEATURES OF THE NEW 2006 RIMS

	ROAD	ASPHALT				
		Cantilever / V-Brake			Disc	
	OPEN SPORT	A 719	A 319	A 119	A 317 Disc	
Rim width						
Technologies						
Material	6106	6106	6106	6106	6106	
Valve hole diameter (in mm)	6,5	8.5 delivered with valve adapter	8.5 delivered with valve adapter	8.5 delivered with valve adapter	8.5 delivered with valve adapter	
ETRTO compatibility	622 x 15	622 x 19	622 x 19	622 x 19	622 x 17	
Recommended tire width (in mm)	19 to 32	28 to 47	28 to 47	28 to 47	28 to 47	
Eyelets	Single	Double	Double	Single	Double	
Average weight (in grams)	490	567	597	540	538	
Finish and drilling	Black	32, 36	32, 36, 40	32, 36	32, 36	-
	Silver	32, 36	36	32, 36	32, 36	32, 36
Recommended spoke nipple length (in mm)	12	12	12	12	12	
Spoke support diameter (in mm)	606	600	600	604	600	
Recommended rim tape (ETRTO x length x thickness)	622 x 18 x 0,6	622 x 20 x 0,6	622 x 20 x 0,6	622 x 20 x 0,6	622 x 20 x 0,6	
Wear indicator	External	Internal	Internal	External	-	

The Mavic rims not mentioned in the above chart have not changed. Their technical features can therefore be found in previous years' technical manuals or on the technical manual website: [www.tech-mavic.com](http://www.tech-mavic.com)