












CLINCHER ROAD RIMS

Type	CLASSIC		PROFILED		
Model	OPEN PRO	MA	CXP 30	CXP 14	CXP 12
Rim section					
Concepts	MAXTAL+SUP+CD+CERAMIC MAXTAL+SUP+CD MAXTAL+SUP +UB CONTROL		SUP + UB Control		
Recommendations For use	Road competition and training - Cyclospor	All types of road use	Road competition and training Cyclospor - Triathlon	Road competition and training - Cyclospor - Triathlon	
Material	MAXTAL	6106	6106		
Diam. of valve hole and valve height	Ø 6,5 mm h = 32 mm		Ø 6,5 mm h ≥ 32 mm		Ø 6,5 mm h = 32 mm
Recommended tire section	18 - 23 mm	19 - 25 mm	18 - 23 mm		19 - 25 mm
Eyelets	Double	Double	Profiled	Profiled	Profiled
Average weight in grams	420	460	550	570	480
Drilling	28.32.36	32.36	24.28.32.36	24.28.32.36 24.28.32	28.32.36 24.28.32
Finish	Hard layer + Ceramic				
	Hard layer		 MA 40		 Ø 700
	Titanium		Titanium		
	Blue	Blue			
	Silver	Silver		Silver	Ø 700 and Ø 650
	Brilliant		Brilliant MA 2		
Spoke nipple Length	12 mm	12 mm	16 mm	16 mm	14 mm
Spoke nipple Material	Nickel-plated brass or anodized aluminum	Nickel-plated brass or anodized aluminum	Nickel-plated brass or anodized aluminum	Nickel-plated brass or anodized aluminum	Nickel-plated brass or anodized aluminum
Spoke support diameter	602 mm	610 mm	584 mm	584 mm (Ø 700) 537 mm (Ø 650)	594 mm (Ø 700) 546 mm (Ø 650)
Rim tape dimensions	Adhesive fabric rim tape 17,5 X 0,6 mm Polypropylene rim tape 17,5 X 0,5 mm				

CLINCHER ROAD OEM RIMS

Type	PROFILED	
Model	CXP 21	CXP 11
Rim section		
Concepts	UB CONTROL	
Ø and valve height	Ø 6,5 mm h = 32 mm	
Tire section	18 - 23 mm	
Length	12 mm	
Spoke nipple Material	Nickel-plated brass (alu not recommended)	
Ø and spoke support	598,5 mm	