

KSYRIUM™ ELITE 650

USE : Use only on a road bike. Any other use (such as on a tandem, cyclo-cross bike, mountain bike...) is strongly inadvisable, and is the sole responsibility of the user, which voids the Mavic warranty.

WHEEL WEIGHT WITHOUT SKEWER :
 Front : 740 g
 Rear : 930 g

REFERENCES :
 Front : 323 355 10
 Rear M10 : 323 356 11
 Rear ED 10 : 323 357 12
 Pair M10 : 323 426 14
 Pair ED10 : 323 427 14

RIMS	COMMERCIAL REFERENCES : Do not use rim tape Front : 323 490 10 Rear : 323 490 13	
	VALVE HOLE Ø Ø : 6,5 mm Length. : = 32 mm 	RECOMMENDED TIRE WIDTH AND PRESSURE Dimensions : Ø 650 only Compatible ETRTO 571 x 13 Recommended tire width : 19 - 28 Recommended tire pressure : See page 05
HUBS	MAINTENANCE : Clean with dry cloth or soap and water. Do not use pressurized water. Caution : The parts on the FTS-L free wheels (pawl assembly, springs, free wheel body) are not compatible with those on the FTS free wheels.	
WHEEL BUILDING	REFERENCE : Front : 323 454 01, length 259 mm (per 9) Rear FWS : 323 455 01, length 279 mm (per 10)	
FEATURES : Black, ultra bladed, stainless steel, straight pull spokes with ABS type of nipples (self-locking).	LACING PATTERN : Front : Radial Rear : Crossed 2 on both sides	TENSION : Front : 100 - 130 kg Rear free wheel side : 130 - 160 kg
ACCESSORIES	WHEEL DELIVERED WITH :	MAINTENANCE
<ul style="list-style-type: none"> • Front quick release skewer : M40350 • Rear quick release skewer : M40351 • Bladed spoke maintenance wrench (with rear wheel) • Free play adjustment wrench : M40123 (with rear wheel) • User guide and warranty card 		For all maintenance procedures (removing the front hub, removing the rear hub, replacing spokes or rims), refer to the 2002 technical manual or our website : www.tech-mavic.com .