














# TECHNICAL FEATURES OF THE NEW 2005 RIMS

		ASPHALT RIMS	MTB RIMS				
			CROSS MOUNTAIN			EXTREME MTB	
			Disc	Cantilever/V-Brake		Disc	
		A 319	XM 317 Disc	XM 317	XM 517	EX 325 Disc	EX 823 Disc
Rim width							
Technologies					 	   	
Material		6106	6106	6106	6106	6106	Maxtal
Valve hole diameter (in mm)		6,5	8,5 delivered with valve adapter	8,5 delivered with valve adapter	8,5 delivered with valve adapter	8,5	6,5 delivered with UST valve M40495
ETRTO compatibility		622 x 19	559 x 17	559 x 17	559 x 17	559 x 25	559 x 23
Recommended tire width (in mm)		28 to 47	1,0 to 2,3	1,0 to 2,3	1,0 to 2,3	2,1 to 3,0	2,1 to 3,0
Eyelets		Double	Single	Single	Single	Single	Fore hollow screws
Average weight (in grams)		597	440	440	410	716	657
Finish and drilling	Ceramic	-	-	-	-	-	-
	Black	32, 36	32, 36		28, 32	32, 36	32, 36
	Silver	32, 36			-	-	-
Recommended spoke nipple length (in mm)		12	12	12	12	12	<b>16</b>
Spoke support diameter (in mm)		600	536	539,5	538	534	528
Recommended rim tape (ETRTO x width x thickness)		622 x 20 x 0,6	559 x 18 x 0,6	559 x 18 x 0,6	559 x 18 x 0,6	559 x 28 x 0,6	<b>Do not use rim tape</b>
Wear indicator		Internal	-	No	No	-	-