









TECHNICAL FEATURES OF THE 2004 ASPHALT RIMS

		ASPHALT RIMS			
		<i>A 119</i>	<i>A 319</i>	<i>A 317 Disc</i>	<i>A 719</i>
Rim width					
Technologies					 
Material		<i>6106</i>	<i>6106</i>	<i>6106</i>	<i>6106</i>
Valve hole diameter (in mm)		<i>6,5</i>	<i>6,5</i>	<i>6,5</i>	<i>6,5</i>
ETRTO compatibility		<i>622 x 19</i>	<i>622 x 19</i>	<i>622 x 17</i>	<i>622 x 19</i>
Recommended tire width		<i>28 - 37 mm</i>	<i>28 - 37 mm</i>	<i>28 - 37 mm</i>	<i>28 - 37 mm</i>
Eyelets		<i>Single</i>	<i>Single</i>	<i>Double</i>	<i>Double</i>
Average weight (in grams)		<i>550</i>	<i>530</i>	<i>490</i>	<i>565</i>
Finish and drilling	Ceramic	-	-	-	-
	Black	<i>32, 36</i>	<i>32, 36</i>	-	<i>36, 40</i>
	Silver	<i>36</i>	<i>36</i>	<i>36</i>	<i>32, 36</i>
Recommended spoke nipple length		<i>12</i>	<i>12</i>	<i>12</i>	<i>12</i>
Spoke support diameter (in mm)		<i>601,5</i>	<i>602</i>	<i>600</i>	<i>599</i>
Recommended rim tape (ETRTO x width x thickness)		<i>622 x 20 x 0,6</i>	<i>622 x 20 x 0,6</i>	<i>622 x 20 x 0,6</i>	<i>622 x 20 x 0,6</i>
Wear & tear indicator		<i>External</i>	<i>Internal</i>	-	<i>Internal</i>

The sale of rims or information in italics is reserved for our OEM customers. However, these rims are available for exchange through our Mavic customer service or the MSC (see list page 51).

TECHNICAL FEATURES OF THE 2004 ROAD RIMS

In 2004, the road rims haven't undergone any modifications.

Therefore, you will find their technical features on the technical manual website www.tech-mavic.com and in the technical manuals from the previous years.