





TREKKING RIMS

| Model | T217 | T238 | T261 | BMX RIMS X ^X |
|-------------------------|---|---|--|---|
| Rim section |  |  |  |  |
| Concepts | SUP + CERA SUP + UB | | | SUP + UB |
| Recommendations for use | All types of use Trekking - Commuting | Trekking - Commuting | | Competition and training on BMX circuits |
| Material | 6106 | | | 6106 |
| Ø of valve hole | 6,5 mm | | | 8,5 mm |
| Eyelets | Double | Simple | Double | Double |
| Average weight in G | 470 480 (Ceramic) | 500 | 540 | 375 |
| Drilling | 36.40 | 36 | 36.40.48 | 32.36 |
| Finish | Hard layer |  | | |
| | + Ceramic |  | | |
| | Hard layer |  | | |
| | Black | | | Black |
| | Silver | Silver | Silver | |
| Length | 12 mm | 12 mm | 12 mm | 12 mm |
| Spoke nipple | Nickel-plated brass or anodized aluminum | Nickel-plated brass or anodized aluminum | Nickel-plated brass or anodized aluminum | Nickel-plated brass or anodized aluminum |
| Spoke support diameter | 600 mm | 603,5 mm | 608 mm | 388 mm |
| Rim tape dimensions | Adhesive fabric or rubber 23 X 0,6 mm | | | 25 x 0,6 mm |
| Width x thickness | Polypropylene rim tape 20 X 1 mm | | | Adhesive fabric or rubber |

OEM TREKKING RIMS

| Model | T 221 |
|-----------------|--|
| Rim section |  |
| Concepts | UB CONTROL |
| Ø of valve hole | 6,5 mm |
| Length | 12 mm |
| Spoke nipple | Nickel-plated brass or anodized aluminum |
| Material | Nickel-plated brass or anodized aluminum |
| Ø spoke support | 602,5 mm |