










TYPE	ADAPTER INFORMATION						DISC INFORMATION					
	REFERENCES	WEIGHT (FIXING NUT NOT INCLUDED).	THICKNESS	MATERIAL	FIXING NUTS	INSTALLATION	MAINTENANCE	NUMBER OF FIXING NUTS ON DISC	FIXING DIAMETER OF DISC	CENTERING DIAMETER OF DISC	FORK SUPPORT / DISC DISTANCE	
AMP	AV.	M 40153	50 g.	16,6 mm	Aluminum alloy,	4 stainless steel screws	<p><b>Tools needed :</b></p> <ul style="list-style-type: none"> <li>• One 4 mm Allen wrench</li> <li>• Grease</li> </ul> <p><b>Installation :</b></p> <p>Procedure to follow on a regular basis especially when using in muddy conditions.</p> <p><b>Tools needed :</b></p> <ul style="list-style-type: none"> <li>• One 4 mm Allen wrench</li> <li>• Grease</li> </ul> <p><b>1 -</b> Disassemble the disc.</p> <p><b>2 -</b> Disassemble the 4 adapter fixing nuts.</p> <p><b>3 -</b> Clean the inside of the adapter, hub body and lip seal M40163 with soapy water.</p> <p><b>4 -</b> Dry all the parts with a cloth.</p> <p><b>5 -</b> Follow the installation instructions to re-install the unit.</p>	3	40 mm	30 mm	9,2 mm	
	AR.	M 40154	34 g.	7,6 mm	anodized black	CHC M5 x 10		3	44 mm	33 mm	19,9 mm	
CODA	AV.	M 40235	40 g.	12,8 mm	Aluminum alloy,	4 stainless steel screws		4	44 mm	30 mm	13 mm	
	AR.	M 40236	45 g.	14,5 mm	anodized black	CHC M5 x 10		4	44 mm	33 mm	13 mm	
FORMULA INTERNATIONAL 98	AV.	M 40333	46 g.	14,5 mm	Aluminum alloy,	4 stainless steel screws		4	40 mm	31 mm	11,2 mm	
	AR.	M 40334	46 g.	12,2 mm	anodized black	CHC M5 x 10		4	40 mm	31 mm	15,2 mm	
HAYES	AV.	M 40159	47 g.	15,6 mm	Aluminum alloy,	4 stainless steel screws		<p><b>4 - Place the lip seal M40163, the shoulder on the wheel side, on the groove of the fork support.</b></p> <p><b>5 -</b> Turn the wheel axle and place the external diameter of the lip seal with your thumb in the adapter groove.</p>         	6	44 mm	33 mm	10,1 mm
	AR.	M 40160	43 g.	12,5 mm	anodized black	CHC M5 x 10			6	44 mm	33 mm	15 mm
HOPE	AV.	M 40161	76 g.	14,5 mm	Aluminum alloy,	4 stainless steel screws			6	84 mm	None	11,2 mm
	AR.	M 40162	60 g.	11 mm	anodized black	CHC M5 x 10			6	84 mm	None	16,5 mm
MAGURA	AV.	M 40151	39 g.	9,8 mm	Aluminum alloy,	4 stainless steel screws			6	44 mm	35 mm	16 mm
	AR.	M 40152	43 g.	11,5 mm	anodized black	CHC M5 x 10			6	44 mm	35 mm	16 mm
ROCK SHOX	AV.	M 40214	48 g.	13,1 mm	Aluminum alloy,	4 stainless steel screws			3	60,3 mm	31 mm	12,7 mm
	AR.	M 40154	34 g.	7,6 mm	anodized black	CHC M5 x 10			3	43,9 mm	33 mm	19,9 mm
SACHS	AV.	M 40157	40 g.	12,1 mm	Aluminum alloy,	4 stainless steel screws	6		44 mm	33 mm	13,7 mm	
	AR.	M 40158	39 g.	10,7 mm	anodized black	CHC M5 x 10	6		44 mm	33 mm	16,8 mm	

NB : Any other type of disc brake that does not appear in the chart above is not compatible with the Mavic adapters nor with the Crosslink® Disc, Crossmax® Disc and Deemax® wheels.