

ADAPTERS FOR DISC BRAKES

| ADAPTERS | | | | | DISCS | | | |
|---------------------------|-------|------------|--------|-----------|-----------------------|-----------------|--------------------|------------------------------|
| Type | | References | Weight | Thickness | Number of fixing nuts | Fixing diameter | Centering diameter | Fork support / Disc distance |
| CODA | Front | M40235 | 40 g | 12,8 mm | 4 | 44 mm | 30 mm | 13 mm |
| | Rear | M40236 | 45 g | 14,5 mm | 4 | 44 mm | 33 mm | 13 mm |
| HAYES | Front | M40159 | 47 g | 15,6 mm | 6 | 44 mm | 33 mm | 10,1 mm |
| | Rear | M40160 | 43 g | 12,5 mm | 6 | 44 mm | 33 mm | 15 mm |
| HOPE | Front | M40161 | 76 g | 14,5 mm | 6 | 84 mm | Aucun | 11,2 mm |
| | Rear | M40162 | 60 g | 11 mm | 6 | 84 mm | Aucun | 16,5 mm |
| INTERNATIONAL 2000 | Front | M40517 | 46 g | 15,4 mm | 6 | 44 mm | 30 mm | 10,5 mm |
| | Rear | M40518 | 40 g | 12,2 mm | 6 | 44 mm | 30 mm | 15,25 mm |
| MAGURA (< 2000) | Front | M40151 | 39 g | 9,8 mm | 6 | 44 mm | 35 mm | 16 mm |
| | Rear | M40152 | 43 g | 11,5 mm | 6 | 44 mm | 35 mm | 16 mm |

NB. :

- The **INTERNATIONAL 2000 model is compatible with the 2000 Hayes, Magura and Shimano brakes discs.**
- All the Mavic brake adapters are delivered with 4 stainless steel CHC M5 x 10 screws for fixing on the Mavic wheels.
- Any other type of brake disc than the ones presented in the above chart is not compatible with the Mavic adapters used with Crosslink® Disc, Crossmax® Disc and Deemax® wheels.

INSTALLATION

Tools needed :

- 1 x 4 mm Allen wrench.
- Grease.

- 1 Remove the original lip seal M40163 of the wheel.
- 2 Mount the adapter and tighten the 4 fixing nuts CHC M5 x 10 with the 4 mm Allen wrench.
Torque : 20 Nm.
- 3 Grease the external diameter of the lip seal M40163.
- 4 Place the lip seal M40163, the shoulder on the wheel side, on the groove of the fork support.
- 5 Turn the wheel axle and place the external diameter of the lip seal with your thumb in the adapter groove.

MAINTENANCE

Follow this procedure on a regular basis especially when using in muddy conditions.

Tools needed :

- 1 x 4 mm Allen wrench.
- Grease.

- 1 Disassemble the disc.
- 2 Disassemble the 4 adapter fixing nuts.
- 3 Clean the inside of the adapter, hub body and lip seal M40163 with soapy water.
- 4 Dry all the parts with a cloth.
- 5 Follow the installation instructions to re-install the unit (see above).