

















WHAT'S NEW FOR 2003

5 new rims are introduced in the 2003 range. Their features are the following:

	ROAD RIMS		MTB RIMS		
	CXP 22 S	CXP22 N (OEM only)	X3.1	D3.1 DISC	X139 DISC (OEM only)
Rim width					
Technologies			    	   	
Material	6106	6106	Maxtal	Maxtal	6106
Valve hole diameter (in mm)	6,5	6,5	6,5	6,5	8,5 with adapter
ETRTO compatibility	622 x 15	622 x 15	559 x 17	559 x 23	559 x 17
Recommended tire width	19 à 28	19 à 28	1,5 à 2,3	2,0 à 2,8	1,5 à 2,3
Eyelets	Single	Without	Fore® hollow screws	Fore® hollow screws	Without
Average weight (in grams)	500	490	465	580	460
Finish and drilling Mavic black	32, 36	32, 36	28, 32	32	32
Recommended spoke nipple length	12	12	16	16	12
Spoke support diameter	596 mm	596 mm	532 mm	532 mm	545,5 mm
Recommended rim tape (ETRTO x width x thickness)	622 x 18 x 0,6	622 x 18 x 0,6	Do not use rim tape	Do not use rim tape	559 x 18 x 0,6
Wear & tear indicator	Integrated in the profile	Integrated in the profile	No	-	-

for building the rims D3.1 Disc and X3.1, consult the building instructions delivered with the rim, the 2002 technical manual, page 21 or the website HYPERTEXT LINK <http://www.tech-mavic.com>.