

		MA3	T519	F519	X618	X221
Section and pression of the tire		See page 22	See page 22	See page 22	See page 22	See page 22
Ø and valve height		Ø = 6,5 mm h = 32 mm	Ø = 6,5 mm h = 32 mm	Ø 6,5 or 8,5 mm*	Ø 6,5 or 8,5 mm*	Ø 6,5 or 8,5 mm*
Ø Spoke support		605 mm	599 mm	536 mm	539 mm	539,5 mm
Spoke length	Length	12 mm				
	Material	Nickle-plated brass or anodized aluminum				
Rim tape		Adhesive fabric 622 x 17 thickness = 0,6 Polypropylene 622 x 18 thickness = 0,5	Polyurethane 622 x 22 thickness = 0,6 Rubber 622 x 23 thickness = 1	Adhesive fabric 559 x 23 thickness = 0,6 Polypropylene 559 x 20 thickness = 1	Adhesive fabric 559 x 23 thickness = 0,6 Polypropylene 559 x 20 thickness = 1	Adhesive fabric 559 x 23 thickness = 0,6 Polypropylene 559 x 20 thickness = 1

* The rims are made with a Ø = 8,5 mm valve hole and can be fitted with a Mavic valve M40381 that reduces the valve hole to Ø = 6,5 mm.